

SANDPAPER & ADHESIVE

PRODUCTS FOR THE HANDYMAN & HOBBYIST

**Standard & custom made discs & sheets
- 110 shapes available**

**Flexible cloth roll material in
short lengths**

Titebond wood glue

**Abrasive belts in various materials for
specific applications**

TRADE QUALITY SUPPLIES FOR THE HANDYMAN AND HOBBYIST

ABRASIVE BELTS & BUFFS

Proudly South Australian Owned and Operated

6 Kiwi Court, Lonsdale SA 5160















Phone: (08) 7288 0933

Email: sales@abrasivebelts.com.au









Website: www.abrasivebelts.com.au

A.B.N. 12 008 090 088

STANDARD SHAPES AVAILABLE

0  <p>Most Popular No Hole Disc diameter 50mm to 770mm</p>	10  <p>Round hole</p>	30  <p>Star shaped hole</p>	GLS 1  <p>dia. 150mm 8 holes dia. 10mm on hole circle dia. 120 mm + 1 centre hole dia. 17 mm</p>	GLS 2  <p>dia. 150mm 8 holes dia. 10mm on hole circle dia. 65mm</p>
	GLS 3  <p>dia. 150mm 6 holes dia. 10mm on hole circle dia. 80mm</p>	GLS 4  <p>dia. 115mm 8 holes dia. 10mm on hole circle dia. 65mm</p>	GLS 5  <p>dia. 125mm 8 holes dia. 10mm on hole circle dia. 65mm</p>	GLS 6  <p>dia. 150mm 8 holes dia. 10mm on hole circle dia. 118mm 6 holes dia. 10mm on hole circle dia. 80mm</p>
GLS 7  <p>dia. 150mm 8 holes dia. 10mm on hole circle dia. 116mm mm, 8 holes dia. 10mm on hole circle dia. 65mm</p>	GLS 47  <p>ø150mm 8 holes ø 9mm on hole circle dia. ø 120mm 6 holes ø 9mm on hole circle dia. ø 80mm + 1 centre hole dia ø 17mm</p>	GLS 15  <p>triangular dia. 96mm 6 holes dia. 8mm on hole circle dia. 52mm</p>	GLS 24  <p>98 x 148mm 7 holes dia. 10mm</p>	GLS 51  <p>dia. 150mm 8 holes dia 10mm on hole circle dia. 120mm, 8 holes dia. 8mm on hole circle dia. 65mm +1 centre hole dia. 10mm</p>

STRIPS AND DISCS

GL 1  <p>115 x 280mm 10 holes dia. 10mm</p>	GL 9  <p>93 x 230mm 8holes dia. 10mm</p>	GL 13  <p>115 x 280mm 8 holes dia. 10mm</p>	GL 17  <p>93 x 180mm 8 holes dia. 10mm</p>	GL 3  <p>93 x 230mm 8 holes dia. 10mm</p>
GL 11  <p>115 x 280mm 14 holes dia. 10mm</p>	GL 15  <p>115 x 230mm 10 holes dia. 10mm</p>	GL 18  <p>80 x 133mm 8 holes dia. 10mm</p>	<p>VELCRO CONVERTER KITS In order to get the kling-on discs or sheets to adhere to the backing plate, we can supply Velcro conversion kits to suit. On one side is the Velcro face and the other is a sticky back.</p>	

ROLLS WITH CLOTH BACKING



LS 309 JF

Abrasive cloth - Roll Width 100mm



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Close
Backing	X-cotton

Advantages: High quality universal abrasive cloth for diverse applications in metal and woodworking, Good price-performance ratio.

GRITS AVAILABLE	80#	100#	120#	150#	240#	320#	400#
1 METRE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5 METRE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

TITEBOND WOOD GLUES



Titebond III is non-toxic, solvent free and cleans up with water. Safer to use than traditional waterproof wood glues. The ultimate in wood glues, ideal for both interior and exterior applications.



Titebond II Premium is a water resistant, one component pre-catalysed Cross-linked PVA adhesive. It may be used for edge gluing and assembly gluing.



Titebond Original, is an aliphatic resin emulsion and used by the makers of fine furniture and musical instrument makers around the world. Excellent sandability, creep and heat resistance and superior solvent resistance.

BELTS



PS 29 F ACT

Abrasive paper, ANTISTATIC

Abrasive belt with outstanding service life. Open coating, antistatic properties as well as ACT prevent premature clogging. The abrasive paper is particularly suitable for processing soft and high-resin woods.



CS 311 Y ACT

Abrasive cloth ANTISTATIC

Open coated aluminium oxide on polyester cloth for calibrating and intermediate sanding in woodworking. ACT and antistatic properties prevent premature clogging.



LS 309 JF

Abrasive cloth

Highly flexible abrasive cloth for highly profiled workpieces for the manufacture of fine surfaces in wood working.

MATERIALS AVAILABLE



Abrasive paper, waterproof

High-quality, tear-resistant, waterproof abrasive paper for working on paint, varnish and filler especially in the car repair sector

Applications

Paint/Varnish/Filler

Bonding agent: Resin

Grain: SiC


Coating: Close

Backing: C

Available grits

60	80	100
120	150	180
220	240	280
320	360	400
500	600	800
1000	1200	1500
2000		

PS 11 C



Abrasive paper, self-fastening

Close coating, tear-resistant backing and high-quality self-sharpening Aluminium oxide for a long service life and high grinding performance for working on metal especially on stainless steel

Applications

Steel

Stainless steel

Bonding agent: Resin

Grain: Alumina zirconia

Coating: Close

Backing: F

Available grits

40	60	80
100	120	150
	180	

PS 21 FK



Abrasive paper, self-fastening

Abrasive paper with close coating and high stock removal rate for an uniform scratch pattern, particularly suitable for working on wood and metal, specially for wood with high resin content

Applications

Wood

Metal Metal

Bonding agent: Resin

Grain: Aluminium oxide

Coating: Semi-open

Backing: E

Available grits

40	60	80
100	120	150
180	240	

PS 22 K



Abrasive paper, self-fastening

High-quality abrasive paper for processing paints, varnish and filler, car repair sector steel

Applications

Paint/Varnish/Filler

Bonding agent: Resin

Grain: Aluminium oxide

Coating: Semi-open

Backing: B/C

Available grits

40	60	80
100	120	150
180	240	320
	400	

*NB Other grades available upon request

PS 33 BK



Non-woven web disc

Applications

Metal/Stainless Steel

Surface Conditioning

Bonding agent: Resin

Grain: Aluminium oxide

Available grits

Coarse - Brown
Medium - Maroon
Very Fine - Blue

NDS 800